







Sylomer[®] Point Bearing PBE

Point bearing for general use

- Universally applicable
- Available in practical formats of 50×50 mm or 100×100 mm and in heights of 12.5 mm and 25 mm
- Natural frequencies from 10.5 Hz
- Load capacity of up to 1,075 kg per discrete bearing

	Type	Maximum load		Natural frequency at maximum load	Packaging unit	Order number
		in kg	in N			
PBE-S 50×50×12.5 mm 	PBE-S-5	6	58	18.5 Hz	1 set (= 48 pcs.)	41930
	PBE-S-13	13	128	17.0 Hz	1 set (= 48 pcs.)	41931
	PBE-S-25	25	245	17.0 Hz	1 set (= 48 pcs.)	41932
	PBE-S-45	48	470	15.5 Hz	1 set (= 48 pcs.)	41933
	PBE-S-95	95	932	15.5 Hz	1 set (= 48 pcs.)	41934
PBE-M 50×50×25 mm 	PBE-M-5	6	58	12.5 Hz	1 set (= 48 pcs.)	41935
	PBE-M-13	12	117	11.5 Hz	1 set (= 48 pcs.)	41936
	PBE-M-25	23	225	11.5 Hz	1 set (= 48 pcs.)	41937
	PBE-M-40	42	412	10.7 Hz	1 set (= 48 pcs.)	41938
	PBE-M-80	80	784	11.0 Hz	1 set (= 48 pcs.)	41939
PBE-L 100×100×12.5 mm 	PBE-L-25	28	274	18.5 Hz	1 set (= 48 pcs.)	41940
	PBE-L-55	55	540	17.0 Hz	1 set (= 48 pcs.)	41941
	PBE-L-110	110	1,079	17.0 Hz	1 set (= 48 pcs.)	41942
	PBE-L-215	215	2,109	15.5 Hz	1 set (= 48 pcs.)	41943
	PBE-L-435	435	4,267	15.5 Hz	1 set (= 48 pcs.)	41944
	PBE-L-780	780	7,652	16.0 Hz	1 set (= 48 pcs.)	41945
	PBE-L-1140	1,075	10,545	15.5 Hz	1 set (= 48 pcs.)	41946
PBE-XL 100×100×25 mm 	PBE-XL-25	27	264	12.5 Hz	1 set (= 48 pcs.)	41947
	PBE-XL-50	52	510	11.5 Hz	1 set (= 48 pcs.)	41948
	PBE-XL-105	101	990	11.5 Hz	1 set (= 48 pcs.)	41949
	PBE-XL-195	195	1,913	10.5 Hz	1 set (= 48 pcs.)	41950
	PBE-XL-385	377	3,698	11.0 Hz	1 set (= 48 pcs.)	41951
	PBE-XL-640	610	5,984	11.0 Hz	1 set (= 48 pcs.)	41952
	PBE-XL-820	820	8,044	10.5 Hz	1 set (= 48 pcs.)	41953

Not held in stock. Delivery time on request (approx. 15 working days from the factory)
 Minimum purchase quantity = packaging unit or multiple thereof



Decoupled air handling unit module



Decoupling of the internal unit of a heat pump