


# Sylomer<sup>®</sup> Strip Bearing SBE

Strip bearing for a broad range of applications

- Universally applicable
- Can also be shortened
- Natural frequencies from 11.5 Hz
- Load capacities up to 930 kg

	Type	Maximum load		Natural frequency at maximum load	Packaging unit	Order number
		in kg	in N			
<b>SBE-L</b> <b>1500 x 60 x 25 mm</b> 	SBE-L-R1	98	961	14.0 Hz	1 set (= 6 pcs.)	<b>45115</b>
	SBE-L-R2	160	1,569	13.0 Hz	1 set (= 6 pcs.)	<b>45116</b>
	SBE-L-R3	247	2,423	12.5 Hz	1 set (= 6 pcs.)	<b>45117</b>
	SBE-L-R4	367	3,600	12.0 Hz	1 set (= 6 pcs.)	<b>45118</b>
	SBE-L-R5	481	4,718	11.5 Hz	1 set (= 6 pcs.)	<b>45119</b>
	SBE-L-R6	930	9,123	11.5 Hz	1 set (= 6 pcs.)	<b>45120</b>

Not held in stock. Delivery time on request (approx. 15 working days from the factory)

## Cutting matrix

	Max. load in kg	Strip length in mm						
		1500	1250	1000	750	500	250	100
Sylomer <sup>®</sup> SBE-L-R1		98	81	65	49	32	16	6
Sylomer <sup>®</sup> SBE-L-R2		160	133	107	80	53	26	10
Sylomer <sup>®</sup> SBE-L-R3		247	205	164	123	82	41	16
Sylomer <sup>®</sup> SBE-L-R4		367	306	245	183	122	61	24
Sylomer <sup>®</sup> SBE-L-R5		481	401	320	240	160	79	31
Sylomer <sup>®</sup> SBE-L-R6		930	775	619	463	308	152	59



Strip bearing for air conditioning (AC) unit



Strip bearing positioned in readiness for a rooftop ventilation unit