

Isotop® ENI

TENDER SPECIFICATION

Manufacturer information

Getzner Werkstoffe GmbH
Herrenau 5
A-6706 Bürs
Austria
www.getzner.com

Brand: **Isotop® ENI - Isolated machine mountings with ball-and-socket joint**

Product properties

| | |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application: | For isolating structure-borne noise and vibrations |
| Efficiency of isolation | >95% (based on an excitation frequency of 50 Hz or 3000 rpm) |
| Consisting of: | High-performance damper made of Sylomer® or Sylodyn® Damper on polyurethane basis, free of plasticisers and substances hazardous to health (e.g. VOC) Polyamide plastic plate M10 threaded rod with ball-and-socket joint, galvanised |
| Natural frequency: | from 10.0 Hz = 600 min ⁻¹ |
| Maximum load bearing: | from 61 kg to 285 kg |
| For the bearing of: | _____ |
| Total weight: | _____ kg |
| Excitation frequency: | _____ Hz or _____ min ⁻¹ |

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® ENI from Getzner Werkstoffe GmbH or equal.

Quantity: pcs

Sum: €
