

# Isotop® SD

## TENDER SPECIFICATION

---

### Manufacturer information

Getzner Werkstoffe GmbH  
Herrenau 5  
A-6706 Bürs  
Austria  
www.getzner.com

---

Brand: **Isotop® SD - Steel spring isolator**

---

### Product properties

|                         |   |
|-------------------------|---|
| Application:            | For isolating structure-borne noise and vibrations  |
| Efficiency of isolation | >99%<br>(based on an excitation frequency of 50 Hz or 3000 rpm)   |
| Consisting of:          | Two spring caps with M10 internal thread (blind rivet nut)<br>Cylindrical coil spring according to DIN 2089<br>CDC-coated or zinc galvanised<br>Optionally with Isotop® FP/K or FP base plate and<br>Isotop® NV height adjustment |
| Natural frequency:      | from 3.2 Hz = 192 min <sup>-1</sup>   |
| Maximum load bearing:   | from 20 kg to 525 kg  |
| For the bearing of:     | _____   |
| Total weight:           | _____ kg  |
| Excitation frequency:   | _____ Hz or _____ min <sup>-1</sup>   |

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® SD from Getzner Werkstoffe GmbH or equal.

---

Quantity: ..... pcs

**Sum:** ..... €

---