

Isotop® DSD-BL

TENDER SPECIFICATION

Manufacturer information

Getzner Werkstoffe GmbH
Herrenau 5
A-6706 Bürs
Austria
www.getzner.com

Brand: **Isotop® DSD-BL - Steel spring block element with Sylodamp® damping core**

Product properties

| | |
|-------------------------|---|
| Application: | For isolating structure-borne noise and vibrations |
| Efficiency of isolation | >98% (based on an excitation frequency of 50 Hz or 3000 rpm) |
| Consisting of: | Isotop® DSD - steel spring isolators with Sylodamp® damping core, CDC-coated Damping core on polyurethane basis, free of plasticisers and substances hazardous to health (e.g. VOC) Steel top plate and base plate, black powder-coated Top plate and base plate with Sylomer® anti-slip plate |
| Natural frequency: | from 4.0 Hz = 240 min ⁻¹ |
| Maximum load bearing: | from 400 kg to 5850 kg |
| For the bearing of: | _____ |
| Total weight: | _____ kg |
| Excitation frequency: | _____ Hz or _____ min ⁻¹ |

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® DSD-BL from Getzner Werkstoffe GmbH or equal.

Quantity: pcs

Sum: €
