

Isotop® DSD

TENDER SPECIFICATION

Manufacturer information

Getzner Werkstoffe GmbH
Herrenau 5
A-6706 Bürs
Austria
www.getzner.com

Brand: **Isotop® DSD - Steel spring isolator with Sylodamp® damping core**

Product properties

| | |
|-------------------------|--|
| Application: | For isolating structure-borne noise and vibrations |
| Efficiency of isolation | >98% (based on an excitation frequency of 50 Hz or 3000 rpm) |
| Consisting of: | Two spring caps with M10 internal thread (blind rivet nut) Cylindrical coil spring according to DIN 2089, CDC-coated with integrated Sylodamp® damping core Damping core on polyurethane basis, free of plasticisers and substances hazardous to health (e.g. VOC) Optionally with Isotop® FP/K or FP base plate and Isotop® NV height adjustment |
| Natural frequency: | from 4.0 Hz = 240 min ⁻¹ |
| Maximum load bearing: | from 24 kg to 650 kg |
| For the bearing of: | _____ |
| Total weight: | _____ kg |
| Excitation frequency: | _____ Hz or _____ min ⁻¹ |

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® DSD from Getzner Werkstoffe GmbH or equal.

Quantity: pcs

Sum: €
