

# Isotop® SE-DE Elevator

## TENDER SPECIFICATION

---

### Manufacturer information

Getzner Werkstoffe GmbH  
Herrenau 5  
A-6706 Bürs  
Austria  
www.getzner.com

---

Brand: **Isotop® SE-DE Elevator - Double-elastic sandwich element for lifts**

---

### Product properties

Application:	For isolating structure-borne noise and vibrations
Efficiency of isolation	>96% (based on an excitation frequency of 50 Hz or 3000 rpm)
Consisting of:	25 mm isolating layer made of Sylomer® or Sylodyn®, category EL-3 according to DIN 8989 Isolating layer on polyurethane basis, free of plasticisers and substances hazardous to health (e.g. VOC) 10 mm pressure distribution plate made of hot-dip galvanised steel, M12 internal thread 60 mm steel intermediate mass 2 mm Sylomer® anti-slip coating
Natural frequency:	from 8.8 Hz = 528 min <sup>-1</sup>
Maximum load bearing:	from 620 kg to 3480 kg
For the bearing of:	_____
Total weight:	_____ kg
Excitation frequency:	_____ Hz or _____ min <sup>-1</sup>

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® SE-DE Elevator from Getzner Werkstoffe GmbH or equal.

---

Quantity: ..... pcs

Sum: ..... €

---