

# AFM 29

## TENDER SPECIFICATION

### Manufacturer information

Getzner Werkstoffe GmbH  
Herrenau 5  
6706 Bürs  
Austria  
www.getzner.com

Brand: **Acoustic Floor Mat 29 - mat out of 100 % polyurethane (PU)**

### Product properties

Application:	highly resilient impact sound insulation to be used below wet or dry screeds		
Impact sound improvement $\Delta L_w$ :	$\geq 29$ dB (measured acc. to EN 10140-3 with evaluation acc. EN 717-2)		
Consisting of:	mat made of mixed-cell, volume-elastic polyurethane material; free from plasticizers and substances hazardous to health; bottom side comes with profile		
Standard form of delivery, mats:	width	750 mm	
	length	1.500 mm	
Thickness:	11 mm		
Load range:	5.000 kg/m <sup>2</sup>		
Dynamic stiffness $s'_t$ :	$\leq 10$ MN/m <sup>3</sup>	(measured acc. to EN 29052-1)	
Compressibility c:	$\leq 0,8$ mm	(measured acc. to EN ISO 29770)	
European Technical Assessment:	ETA-21/0143		

The impact sound insulation mat is to be laid butt-jointed and bonded together at the joints using suitable adhesive tape.

A European Technical Assessment (ETA) must be submitted for deviating products.

Offered product: Acoustic Floor Mat 29 from Getzner Werkstoffe GmbH or equal.

Quantity:	.....	m <sup>2</sup>
Sum:	.....	€