

# Isotop® SE pro

## TENDER SPECIFICATION

---

### Manufacturer information

Getzner Werkstoffe GmbH  
Herrenau 5  
A-6706 Bürs  
Austria  
www.getzner.com

---

Brand: **Isotop® SE pro - Sandwich element**

---

### Product properties

Application:	For isolating structure-borne noise and vibrations
Efficiency of isolation	>95% (based on an excitation frequency of 50 Hz or 3000 rpm)
Consisting of:	37,5 mm isolating layer made of Sylomer® or Sylodyn®, one-ply Isolating layer on polyurethane basis, free of plasticisers and substances hazardous to health (e.g. VOC) 10 mm pressure distribution plate made of hot-dip galvanised steel, M12 internal thread 6 mm Sylomer® anti-slip coating Optionally with base plate or base and pressure plate
Natural frequency:	from 7,9 Hz = 474 min <sup>-1</sup>
Maximum load bearing:	from 90 kg to 2250 kg
For the bearing of:	_____
Total weight:	_____ kg
Excitation frequency:	_____ Hz or _____ min <sup>-1</sup>

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® SE pro from Getzner Werkstoffe GmbH or equal.

---

Quantity: ..... pcs

Sum: ..... €

---