

Ecolay

TENDER SPECIFICATION

Manufacturer information

Getzner Werkstoffe GmbH
Herrenau 5
6706 Bürs
Austria
www.getzner.com

Brand: **Ecolay - roll out of elastomer-textile with fabric coating**

Product properties

Application:	impact sound insulation to be used below wet or dry screeds as well as an underlay for finish floors		
Impact sound improvement ΔL_w :	≥ 19 dB (measured acc. to EN 10140-3 with evaluation acc. EN 717-2)		
Consisting of:	roll of recycled elastomer granules laminated in fleece; free from plasticizers and substances hazardous to health;		
Standard form of delivery, mats:	width	1.000 mm	
	length	10.000 mm	
Thickness:	3 mm		
Load range:	3.000 kg/m²		
Dynamic stiffness s'_t :	≤ 55 MN/m³	(measured acc. to EN 29052-1)	
Compressibility c:	$\leq 1,0$ mm	(measured acc. to EN ISO 29770)	
European Technical Assessment:	-		

The impact sound insulation mat is to be laid butt-jointed and bonded together at the joints using suitable adhesive tape.

A European Technical Assessment (ETA) must be submitted for deviating products.

Offered product: Ecolay from Getzner Werkstoffe GmbH or equal.

Quantity: m²
Sum: €