

AFM 33

TENDER SPECIFICATION

Manufacturer information

Getzner Werkstoffe GmbH
Herrenau 5
6706 Bürs
Austria
www.getzner.com

Brand: **Acoustic Floor Mat 33 - mat out of 100 % polyurethane (PU)**

Product properties

Application:	high-performance impact sound insulation to be used below floating screeds	
Impact sound improvement ΔL_w :	≥ 33 dB (measured acc. to EN 10140-3 with evaluation acc. EN 717-2)	
Consisting of:	mat made of mixed-cell, volume-elastic polyurethane material; free from plasticizers and substances hazardous to health; bottom side comes with profile	
Standard form of delivery, mats:	width	750 mm
	length	1.500 mm
Thickness:	16 mm	
Load range:	2.500 kg/m ²	
Dynamic stiffness s'_t :	≤ 9 MN/m ³	(measured acc. to EN 29052-1)
Compressibility c:	$\leq 1,0$ mm	(measured acc. to EN ISO 29770)
European Technical Assessment:	ETA-17/0243	

The impact sound insulation mat is to be laid butt-jointed and bonded together at the joints using suitable adhesive tape.

A European Technical Assessment (ETA) must be submitted for deviating products.

Offered product: Acoustic Floor Mat 33 from Getzner Werkstoffe GmbH or equal.

Quantity: m²
Sum: €