Installation guideline g-fit Gear T300

getzner engineering a quiet future



 Please read carefully through the installation guide before you start the installation.

Requirements regarding the surface (parquet, tiles, carpet, timber, ...)

- · Permanently dry
- Clean-swept



2) Before starting the installation work please check if the delivery is complete and flawless. The dimensions of the pedestals and rolls must be checked beforehand. The inlay frame of the pads has to be cut to the requested size (if not suitable). Therefore cut the selected frame with a knife along the 4 fixed points and break it out of the frame.



3) Please position the treadmill on the foreseen place in the room. The treadmill must be adjusted to an inclination of 0°. Lift the front side of the treadmill to position the pads beneath. Start with one side first, and adjust the second side in the next step. Please keep in mind that softer materials must have fullsurface contact to the floor.



4) The bigger pair of pads has to be used for the vertically adjustable front part. The rolls of the treadmill must be placed in longitudinal direction to the front inlay edge.



5) Please note that the pad should be placed in the center of gravity of the loading even if the position of the treadmill is in max inclination.

If any tilting arises, the position of the pad must be adjusted accordingly.



6) In the last step lift the rear part of the treadmill and place the smaller pair of the T300 pads with the fitting inlay underneath. The treadmill is now ready for usage.

engineering a guiet future

Installation guideline g-fit Gear T300 en © Copyright by Getzner Werkstoffe GmbH 10-2018