

# Optimisation of Turnouts with Elastic Bearings





# Solutions for ballast protection



The inhomogenous load distribution of passing trains causes high dynamic forces in turnouts. As a result, numerous factors increase maintenance costs: The ballast is subjected to heavy loads and wear. This produces cavities beneath the sleepers and the entire turnout can tilt. Additionally, damages to other components such as the frog and rails occur.



Inhomogeneous load distribution in the turnout causes ballast wear and "white spots".



High dynamic forces frequently lead to broken rails.

# Solutions for vibration isolation



When trains pass through, vibrations and noise are transferred to the surrounding area - both in slab track and ballasted track. Moreover, the vibrations affect the entire superstructure.



Damage to rails and the turnout frog



Reduced quality of life without vibration isolation

# Solutions for ballast protection





### **Under Ballast Mats**

Optimum ballast bedding and load transfer. Effective vibration protection.



### **Under Sleeper Pads**

Increased track quality, longer ballast service life and fast installation.

### Advantages of the solutions

- Higher availability and longer service life of the railway line
- Less wear to turnout components such as frog or rails
- Longer ballast service life
- Reduced maintenance costs
- Lower life cycle costs



#### Rail Pads

Improved load distribution for reduced wear to the superstructure. High mechanical load capacity.



### **Baseplate Pads**

Reduced vibrations and improved load distribution in the case of slab track systems.

### Less wear

The introduction of defined elasticity with Sylomer® and Sylodyn® evens out asymmetrical loads in the area of the turnout. This reduces wear and maintenance costs significantly. Tamping intervals can be extended by at least 100 %.



Optimised turnout with Under Sleeper Pads



Turnout without elastic bearing



### China | CRC China Railway Corporation Rail Pads

- Higher availability of heavy haul tracks
- Longer service life of rails
- Lower life cycle costs

### References (extract) Solutions for ballast protection

- DB, DE, since 2004
- ÖBB, AT, since 2005
- ADIF, ES, since 2008
- SNCF, FR, since 2011
- RFI, IT, since 2014
- Trafikverket, SE, since 2015




### Austria | ÖBB Under Sleeper Pads

- Reduced ballast wear
- More homogenous load distribution
- Longer service life of the turnout

### The perfect mix of materials selected with the Finite Element Method

sing the Finite Element Method, the effects of a train passing over a turnout are simulated precisely, taking into account all geometric boundary conditions. This results in an optimum mix of various elastic elements such as different types of Under Sleeper Pads.



Getzner simulation tool for the turnout

### Solutions for vibration isolation





# Mass-Spring Systems (full surface, strip- or point-bearing)

Highly effective vibration protection and greater elasticity for the superstructure.



#### **Under Ballast Mats**

Optimum ballast bedding and load transfer. Effective vibration protection.

### Advantages of the solutions

- Better living conditions and acceptance among people living near railway lines
- Greater flexibility in track/ installation planning
- Higher availability of the railway line
- Less wear to the superstructure
- Greater comfort for passengers
- Vibrations reduced by up to 95%



**Insertion Pads for Sleeper Boots** Reduced structure-borne noise, emission particularly in tunnels.



### **Baseplate Pads**

Reduced vibrations and improved load distribution in the case of slab track systems.

### More elasticity for greater comfort

lexible solutions from Getzner provide targeted elasticity and reduced changes in stiffness - for turnouts in both slab tracks and ballasted superstructures. Railway lines thereby create less vibration and noise.



Turnout mounted on a Mass-Spring System



### Brazil | Salvador de Bahia, Line 1 Insertion Pads for Sleeper Boots and Mass-Spring System

- Maintenance-free Sylodyn® bearings
- Effective protection against vibrations and structureborne noise
- Better living and working conditions for residents

# References (extract) Solutions for vibration isolation

- London Underground, GB, 2011
- ÖBB, entrance to Brenner Base Tunnel, AT, 2012
- Metro Sao Paulo, BR, 2013
- Metro Madrid, ES, 2014
- SBB, Gotthard Base Tunnel, CH, 2016
- Metro Istanbul, TR, 2018




### China | Zhangjiawan Depot, Metro Beijing, Line 7 Under Ballast Mats

- Increased elasticity
- Vibration protection for noise-sensitive buildings
- Increased track quality

### Precise simulation for reduced changes in stiffness

The optimum elasticity determined using the Finite Element Method reduces the changes in stiffness caused by the turnout geometry. The smooth passage of the train minimises vibrations and protects the superstructure.



Getzner simulation tool for the turnout





Large scale test rig

Installation of under ballast mats

### Developed, tested and installed by experts

Products from Getzner are continually subjected to strict quality testing, even during the production process. Their reliability is rigorously tested, not only on the large scale test rig in-house, but also frequently by independent external institutes such as the Technical University of Munich (Chair and Institute of Road, Railway and Airfield Construction).

### Comprehensive range of services


An excellent product can only reach its full potential when it is used correctly. Experts from Getzner support customers all the way from precise deflection calculations through the optimum material choice, to installation supervision and approval on site.














www.getzner.com/turnouts



